





























Specification Information for Scotchlok™ Insulation Displacement Connectors for Communication

Connector	Type Connector	Features	Maximum Insulation	AWG (mm2) Wire Range	Operating Temp.	UL, CSA or CE Certified	Suggested 3M Tool
U1B 		Full pair	0.125" (3,18 mm)	16-19 (1,3-0,9) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM
U1R 		Full pair	0.125" (3,18 mm)	19-24 (0,9-0,5) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM
UAL 		For aluminum copper	0.082" (2,08 mm) Outside port 0.076" (1,93 mm) Center port	17-20 (1,15-0,8) Solid wire 19-24 (0,9-0,5) Solid copper	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UB2A 		RUS Listed, full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UB2A-D 		RUS Listed, full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UG 		Moisture- resistant seal	0.066" (1,67 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UP2 		Dry flame retardant	0.060" (1,52 mm)	22-26 (0,7-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UP3 		Dry flame retardant	0.066" (1,67 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UR 		Moisture- resistant seal	0.066" (1,67 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UR2 		RUS Listed, full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UR2-D 		Dry full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UY 		Moisture- resistant seal	0.060" (1,52 mm)	22-26 (0,7-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UY2 		RUS Listed, full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y
UY2-C 		Dry full featured*	0.082" (2,08 mm)	19-26 (0,9-0,4) Solid wire	-40 to 285°F (-40 to 140°C)	N/A	E-9BM E-9Y

Note: solid wires only.

*Full Featured – Offers full wire range capability, increased port size to accommodate up to 0.82" (2,08 mm) insulation sizes, double elements in all products and a solvent-resistant plastic construction.

Ordering Information for Scotchlok™ Insulation Displacement Connectors for Communication

Product Number	UPC (054007-)	Inner Unit Pack	Distributor Order Qty.
U1B	71340	—	1,000 bulk
U1R	56388	100/box	1,000 case
UAL	27827	100/box	1,000 case
	27828	10 conn./cart. - 10 cart./pack - 10 pack/case	1,000 connectors each
UB2A	92693	100/box	1,000 case
	92695	—	1,000 bin
	92696	500/bag	5,000 bulk
UB2A-D	92694	100/box	1,000 case
	92698	—	1,000 bin
	92697	1,000/box	5,000 bulk
UG	56391	100/box	1,000 case
	33280	—	5,000 bulk
	27814	20/bag	1,000 bin
UP2	32698	16 conn./cart. - 10 cart./pack - 10 pack/case	1,600 connectors each
	33420	100/box	5,000 bulk
	33428	N/A	1,000 bin
UP3	33429	N/A	1,000 bin
	33419	N/A	5,000 bulk
	32700	10 conn./cart. - 10 cart./pack - 10 pack/case	1,000 connectors each
UR	33277	—	5,000 bulk
	27815	N/A	1,000 bin
	56390	100/box	1,000 case
	27816	10 conn./cart. - 10 cart./pack - 10 pack/case	1,000 connectors each
UR2	68540	—	1,000 bin
	68538	100/box	1,000 case
	68539	500/box	5,000 bulk
	68541	10 conn./cart. - 10 cart./pack - 10 pack/case	1,000 connectors each
UR2-D	71473	N/A	1,000 bin
	71474	N/A	5,000 bulk
	71475	10 conn./cart. - 10 cart./pack - 10 pack/case	1,000 connectors each
UY	33278	1,000/box	5,000 bulk
	14929	N/A	1,000 bin
	14911	100/box	1,000 case
	27817	16 conn./cart. - 10 cart./pack - 10 pack/case	1,600 connectors each
UY2	68536	N/A	1,000 bin
	68537	100/box	1,000 case
	68535	N/A	5,000 bulk
	68534	12 conn./cart. - 10 cart./pack - 10 pack/case	1,200 connectors each
UY2D	71476	N/A	1,000 bin
	71477	N/A	5,000 bulk
	71478	12 conn./cart. - 10 cart./pack - 10 pack/case	1,200 connectors each