



## WIRE MESH CABLE GRIPS

### Bus Drop Grips

Tuff Seal Bus Drop Grips support flexible cord or cable at the bus duct when power is supplied from an overhead source. Suitable for indoor use only, these grips relieve tension and absorb vibration which protects the cable. These grips are woven of galvanized steel wire and are offered with either a single eye or universal bale.

### Bus Drop Safety Springs

Tuff Seal Bus Drop Safety Springs are used with the Bus Drop Grips to relieve sudden strain on cord or cable overhead systems. These safety springs can be used with single-eye type grips by disassembling the drawbar from the coil, placing it through the eye and replacing the drawbar.

#### NOTES

for stainless Bus Drop Grips use 74xx-xxx

*Example:* 7304-009 in stainless is 7404-009

Information on Approximate Breaking Strength on page 59 in Tuff-Seal Technical Reference Section.

### BUS DROP GRIPS




Cable Range	Part Numbers	Description	Approx.* Breaking Strength	Length Eye	(IN.) Mesh
<b>SINGLE EYE—WIDE RANGE</b>					
.22 – .32	7304-001R	BD022	350	3	3 1/2
.30 – .43	7304-002R	BD030	450	4	4
.41 – .56	7304-003R	BD041	550	6	4 3/4
.53 – .73	7304-004R	BD053	1000	7	6
.70 – .85	7304-005R	BD070	1400	7	6 3/4
.82 – 1.00	7304-006R	BD082	1400	8	8
.96 – 1.25	7304-007R	BD096	1500	9	9 1/2

#### UNIVERSAL BALE—WIDE RANGE

.22 – .32	7304-009R	BD022-UB	350	9	3 1/2
.30 – .43	7304-010R	BD030-UB	450	10	4
.41 – .56	7304-011R	BD041-UB	550	12	4 3/4
.53 – .73	7304-012R	BD053-UB	1000	13	6
.70 – .85	7304-013R	BD070-UB	1400	13	6 3/4
.82 – 1.00	7304-014R	BD082-UB	1400	14	8
.96 – 1.25	7304-015R	BD096-UB	1500	15	9 1/2

### BUS DROP SAFETY SPRINGS



Description	Part Numbers	Maximum Deflection	Breaking Strength	Approx.* Length (No Load)	Diameter
40 lb. Spring	203-02-001	2 5/8" at 40 lbs.	500	8 1/4"	3/4"
80 lb. Spring	203-02-002	3 1/8" at 80 lbs.	850	8 1/4"	1"



# WIRE MESH PRODUCTS

## CROSS REFERENCE

### BUS DROP GRIPS, SINGLE EYE—WIDE RANGE

Cable Range	Remke	(Bryant) Economy	Pass & Seymour Slater/Flexcor	(Hubbell) Kellems	Woodhead
.22 – 0.32	7304-001	BDS25-U	FC22	073-04-1276	36560
.30 – 0.43	7304-002	BDS37-U	FC30	073-04-1277	36562
.41 – 0.56	7304-003	BDS50-U	FC40	073-04-1278	36564
.53 – 0.73	7304-004	BDS62-U	FC52	073-04-1279	36567
.70 – 0.85	7304-005	BDS75-U	FC70	073-04-1280	36569
.82 – 1.00	7304-006	BDS87-U	—	073-04-1281	36571
0.96 – 1.25	7304-007	BDS100-U/ BDS118-U	FC94	073-04-1282	36574
—	—	—	—	—	—

### BUS DROP GRIPS, UNIVERSAL BALE—WIDE RANGE

Cable Range	Remke	(Bryant) Economy	Pass & Seymour Slater/Flexcor	(Hubbell) Kellems	Woodhead
.22 – 0.32	7304-009	BDS25-H	FC22-LB	073-04-1283	36580
.30 – 0.43	7304-010	BDS37-H	FC30-LB	073-04-1284	36582
.41 – 0.56	7304-011	BDS50-H	FC40-LB	073-04-1285	36584
.53 – 0.73	7304-012	BDS62-H	FC52-LB	073-04-1286	36587
.70 – 0.85	7304-013	BDS75-H	FC70-LB	073-04-1287	36589
.82 – 1.00	7304-014	BDS87-H	—	073-04-1288	36591
.96 – 1.25	7304-015	BDS100-H/ BDS118-H	FC94-LB	073-04-1289	36594
—	—	—	—	—	—

### BUS DROP SAFETY SPRINGS

Description	Remke	(Bryant) Economy	Pass & Seymour Slater/Flexcor	(Hubbell) Kellems	Woodhead
40 lb. Spring	203-02-001	S-40	203-02-001	203-02-001	36237
80 lb. Spring	203-02-002	S-80	203-02-002	203-02-002	36238