

L-14

Class I, Div. 1 and 2,
Groups C,D
NEMA 7  CD

20 Amp CPS Factory Sealed Receptacles: Explosion-Proof

Dead-Front Safety Construction—Grounding thru Extra Pole and Shell.

		Type	Wire/Pole	Hub Size, Inches	Catalog Number
CPS Receptacles 120-240V A.C., 20A at 1 H.P.; 20A at 24V D.C.					
	CPSE	Dead-End	2W,3P	1/2 3/4	CPSE-2350 CPSE-2375
	CPSC	Feed-Thru	2W,3P	1/2 3/4	CPSC-2350 CPSC-2375
CPS Receptacle 15° Angle Type 120-240V A.C., 20A at 1 H.P.; 20A at 24V D.C.					
	CPSA	Dead-End	2W,3P	1/2 3/4	CPSA-2350 CPSA-2375
CPS Receptacle Only (Replacement) with Mounting Box					
	CPSR	CPSR	2W,3P		CPSR-23
CPS Receptacles with EFD Mounting Boxes 120-240V A.C., 20A at 1 H.P.; 20A at 24V D.C.					
Single Gang					
	CPC1	Dead-End	2W,3P	1/2 3/4 1	CPE1-2350 CPE1-2375 CPE1-23100
		Feed-Thru	2W,3P	1/2 3/4 1	CPC1-2350 CPC1-2375 CPC1-23100
Two Gang					
	CPC2	Dead-End	2W,3P	1/2 3/4 1	CPE2-2350 CPE2-2375 CPE2-23100
		Feed-Thru	2W,3P	1/2 3/4 1	CPC2-2350 CPC2-2375 CPC2-23100
CPS Receptacle Only (Replacement) with EFD Mounting Box					
		CPR	2W,3P		CPR-23
CPP Plugs for use with Receptacles Above					
		Plug amperes match receptacle ratings	2W,3P	Cable Dia., Inches .536 to .639	CPP-2023