

OB/SB-2

Weatherproof Incandescent Fixtures

Rugged, seamless die cast construction. Factory assembled with guard, 120Volt rated. Ground screw, closure plugs and mounting lugs included. 12" leads with 150°C supply wire included. Use with medium base incandescent lamps. Grey color.



WFA1050G
WFA1075G
WFA2050G
WFA2075G



WFC1050G
WFC1075G
WFC2050G
WFC2075G



WFW1050G
WFW1075G
WFW2050G
WFW2075G

Catalog Number	Mounting Style	Hub Size	No. of Hubs	Wattage	Packaging	Wt per 100 (lbs)	Case Qty
WFA1050G	Pendant	1/2"	1	100	Boxed	267	1
WFA1075G	Pendant	3/4"	1	100	Boxed	267	1
WFA2050G	Pendant	1/2"	1	200	Boxed	410	1
WFA2075G	Pendant	3/4"	1	200	Boxed	410	1
WFC1050G	Ceiling	1/2"	5	100	Boxed	267	1
WFC1075G	Ceiling	3/4"	5	100	Boxed	267	1
WFC2050G	Ceiling	1/2"	5	200	Boxed	420	1
WFC2075G	Ceiling	3/4"	5	200	Boxed	420	1
WFW1050G	Wall	1/2"	5	100	Boxed	380	1
WFW1075G	Wall	3/4"	5	100	Boxed	380	1
WFW2050G	Wall	1/2"	5	200	Boxed	510	1
WFW2075G	Wall	3/4"	5	200	Boxed	510	1

OB/SB-2

Weatherproof Boxes, Covers, Lampholders and Lighting Fixtures

Applications:

Use in branch circuit wiring for wet, damp, or dry locations

- May be used as a junction box or a device box for switches, receptacles, GFCI's, etc.
- Lampholders are for use in exterior and interior applications to provide safety and security for driveways, doorways, and walkways.
- Lighting Fixtures are for use in areas where moisture ingress is a concern such as construction sites, tunnels, bridges, subways.

Features and Benefits:

- Rugged continuous and seamless die cast construction prevents entry of dirt, dust and moisture.
- Powder coating is applied for uniform cosmetic coating and weatherproof durability.
- Mounting can be achieved with mounting lugs (provided) or by using the integral mounting knockouts.
- Smooth, accurately tapped hubs prevent wire abrasion.
- Clear UL marking and volumetric marking cast into each box and extension ring facilitate electrical inspection.
- Continuous box and cover compression ensure complete sealing at gasket interface to prevent moisture entry.
- Lockable covers and covers with integral devices are offered.
- Closure plugs (2), mounting lugs (2) and green ground screw provided with each box.
- Mounting hardware and gasket provided with each cover.
- Locking swivel knuckle on lampholders permits positive lamp positioning and accurate directional aiming.
- Lampholders are supplied with all hardware including locknuts, porcelain sockets and internal gaskets for reliability and weather protection.
- Photocells and lampholders are supplied with long leads (4" from the end of the knuckle) to facilitate wiring.
- Lighting fixtures are factory assembled and fully gasketed to ensure fast and easy installation.



Most of the boxes, covers, and lampholders are individually shrink wrapped, labeled and bar coded for ease of handling and identification.



Sturdy corrugated boxes with easy lift off top facilitate merchandising.

- Complete installation instructions are provided with each item.
- In-Use covers include: patented inserts and comply with NEC® requirements.
- Most of the boxes, covers, and lampholders are individually shrink wrapped, labeled and bar coded for ease of handling and identification.
- Lighting fixtures are individually boxed, labeled, and bar coded for ease of handling and identification.
- Well-marked outer boxes combined with shrink wrapping facilitate merchandising.

Materials:

- Boxes, Extensions, Covers, Lamp-

holders, Lighting Fixtures, and Closure plugs: Zinc Die Cast.

- In-Use covers: polycarbonate.
- Lugs: Stamped Aluminum (One and two gang boxes), Integrally cast (round boxes).
- Cover screws: Plated Steel.
- Gaskets: Closed cell foam (covers), Fiber (lampholders), Closed cell foam or Fiber (lighting fixtures).
- Glass: Annealed glass.
- Sockets: Porcelain (lampholders and lighting fixtures).

Compliances:

- UL and CUL Listed.