SUPER-SAFEWAY® GRIPS

WIDE-RANGE GRIPS

(File No. LR32159)



Wide-Range Grips are recommended for use in wiring of enclosures, power boxes, machine tools, and power centers. Includes insulated bushing.

NPT Size (Inches)	Cable Dia. Range (Inches)	Woodhead Numbers	Product Selection Numbers	Mesh Length @ Nom. Dia. (Inches)	Min. Btwn. Grips (Inches)
1/2	0.22–0.32	36501	WRP-022	3-1/4	1-1/4
1/2	0.30–0.43	36503	WRP-030	3-3/4	1-1/4
1/2	0.40–0.54	36505	WRP-040	4-3/4	1-1/4
3/4	0.52–0.73	36508	WRP-052	5-3/4	1-1/2
1	0.70–0.97	36512	WRP-070	7	1-7/8
1-1/4	0.94–1.25	36515	WRP-094	9	2-3/8
1-1/2	1.20–1.50	36516	WRP-120	11-3/4	2-5/8
2	1.40–1.75	36517	WRP-140	13-1/4	3-1/4
2-1/2	1.62–2.00	36518	WRP-162	13-1/2	3-5/8
2-1/2	2.00–2.45	36519	WRP-200	13-3/4	3-5/8

Super-Safeway is a registered trademark of Woodhead Industries, Inc.

Product Group	Description	Material
PULLING GRIPS		
	PJ junior duty	Galvanized steel wire
	PL light duty	Galvanized steel wire
	PM medium duty	Galvanized steel wire
	P heavy duty	Galvanized steel wire
	PS heavy duty swivel	Galvanized steel wire
	PR-MS multi-weave, rotating eye	Galvanized steel wire
	PF-MS multi-weave, flexible eye	Galvanized steel wire
	PHS high strength	Galvanized steel wire
	SCK slack, offset eye	Galvanized steel wire
	SSK slack, offset eye	Galvanized steel wire
	SRK slack, offset eye	Galvanized steel wire
	RC rope puller	Galvanized steel wire
	RT rope/splicing tube grip	Galvanized steel wire
STRAIN-RELIEF GRIPS		
	Wide range (with gasket)	Galvanized steel wire
	Deluxe cord grips	Stainless steel wire
	Liquid-tight (metallic cond.)	Stainless steel wire
	Liquid-tight (non-metallic cond.)	Stainless steel wire
	MAX-LOC® cord grips	Nylon
	Deluxe cord grips (non-metallic)	Non-conductive
	Bus-drop grips	Galvanized steel wire
	Safety springs	Spring steel
SUPPORT GRIPS		
	Standard support grips	Tinned bronze or stainless steel[1]

[1] Stainless steel available on request. Contact your Woodhead Representative.

MAX-LOC is a registered trademark of Woodhead Industries, Inc.